


Industrial Series

2 station 16 ft.



Whatever Your Event

**PORTABLE RESTROOM
TRAILERS, LLC**

Mobile Restroom Trailers

We Have The Right Solution

Decon

STANDARD SPECIFICATIONS

16' x 8' Decon Trailer

CLIMATE CONTROL:

One (1) roof mounted A/C unit with heat strip – 13,500 BTU cooling and 5,600 BTU heating

One (1) electric wall heater installed in the dirty room (1500 watts)

DECON EQUIPMENT:

700 CFM negative air unit with HEPA filtration, all aluminum, installed in the dirty room with 3-way switch

One (1), micron filtration system for asbestos, and one lead filtration system with ½ HP pump, both are fully automatic and installed in the utility compartment

CHASSIS:

Heavy duty 8" x 4" x 10 lb. structural steel wide flange main beams; 2" x 2" x 16 ga. steel tubing floor joists 16" o.c.; 2-5/16" A frame coupler with 10,000 lb. tongue jack; high speed 5,200 lb. tandem axles with electric brakes and break away kit; 225x75x15 D load range tires with 15" wheels;

STRUCTURE:

¾" Advantek sub-flooring; seamless, non-slip, TPO floor; ACSI stick built construction.; .040 thick, smooth aluminum exterior siding with baked enamel finish; white FRP on interior walls and ceiling, all seams are silicone sealed for a water resistant interior; R-11 insulation – floors, walls and ceiling; one (1) make up air vent for FA700 neg air unit; two (2) heavy duty ACSI SIP aluminum framed doors with full length continuous hinge and lever set door locks (30" x 79"); .040 thick, seamless aluminum roof fastened to the perimeter aluminum top rail, all fasteners are located outside the trailer body.

PLUMBING:

Two (2) stall aluminum shower module with three flap OSHA compliant air lock curtains

A 40 gallon electric water heater will be installed in the utility compartment.

80 gallon polyethylene holding tank mounted under trailer

Floor drains installed in clean and dirty sides plumbed to holding tank

A stainless steel sink will be recessed into the side of the trailer and plumbed to the holding tank, includes a lockable door (exterior hand wash unit)

Plumbing supply lines will consist of a high density crossed linked polyethylene tubing with brass swaged fittings

Exterior plumbing supply lines and holding tank will be heat traced and insulated

ELECTRICAL:

Three (3) fluorescent light fixtures, rated for wet location, operated by three way switch

Heavy duty load center with breakers 100 amp 240v/120v single phase 60 Hz

Four duplex receptacles, GFI protected, installed in the clean and dirty rooms

Washer and dryer connections included