

Industrial Series

4 station 24 ft.



Whatever Your Event
**PORTABLE RESTROOM
TRAILERS, LLC**
Mobile Restroom Trailers
We Have The Right Solution

Decon

STANDARD SPECIFICATIONS

24' x 8' Decon Trailer

CLIMATE CONTROL:

One (1) roof mounted A/C unit with heat strip – 13,500 BTU cooling and 5,600 BTU heating

One (1) wall mounted electric heater installed in the dirty room (1500 watts)

DECON EQUIPMENT:

700 CFM negative air unit with HEPA filtration, all aluminum, installed in the dirty room with 3-way switch

One (1) dual filtration system for asbestos and lead with ½ HP pump, both are fully automatic and installed in their own compartment

CHASSIS:

Heavy duty 8" x 4" x 10 lb. structural steel wide flange main beams; 2" x 2" x 16 ga. primed steel tubing floor joists 16" o.c.; 2 5/16" spring action 12K coupler with 10,000 lb. tongue jack; high speed 6,000 lb. tandem axles with electric brakes and break away kit; ST235-85R-16 E load range tires with 16" wheels; FMVSS compliant running lights

STRUCTURE:

¾" Advantech T&G plywood sub-flooring; seamless, non-slip, tpo floor covering; ACSI stick built construction; .040 thick, smooth aluminum exterior siding with WHITE baked enamel finish; fiberglass reinforced plastic (FRP) on interior walls and ceiling, all seams are silicone sealed for a water resistant interior; R-11 insulation – floors, walls and ceiling; one (1) make up air vent for FA700 neg air unit; two (2) heavy duty ACSI SIP aluminum framed doors with full length continuous hinge and lever set door locks (30" x 79"); .040 thick, seamless aluminum roof fastened to a heavy duty perimeter aluminum top rail, all fasteners are located outside the trailer body.

PLUMBING:

Four (4) stall, aluminum shower module with three flap OSHA compliant air lock curtains

A 50 gal. electric water heater installed in its own compartment

80 gallon polyethylene holding tank mounted under trailer

Exterior hand wash unit with stainless steel sink plumbed to the holding tank, recessed into side of trailer with lockable

door (exterior hand wash unit)

Floor drains installed in clean and dirty sides plumbed to holding tank

Plumbing supply lines will consist of a high density crossed linked polyethylene tubing with brass swaged lock fittings

Exterior plumbing supply lines and holding tanks will be heat traced and insulated

ELECTRICAL:

Four (4) fluorescent light fixtures, rated for wet location, operated by three way switch

Heavy duty load center with breakers 100 amp 240v/120v single phase 60 Hz

Four (4) duplex receptacles, GFI protected, installed in the clean and dirty rooms

Washer and dryer connections included

FURNITURE:

Twelve (12) personnel lockers (12" x 18" x 36") fastened to walls in clean room

Two (2) Aluminum benches with fabricated aluminum pedestals

Twelve (12) clothing hooks mounted on walls, 6 in dirty side and 6 in clean side

MISC:

Heavy duty steel steps, fully supported by the chassis, with fold out aluminum handrails located at each entry/exit door